


# DEFEND 1050 SPECIFICATIONS



*The Novaerus Defend 1050 has been cleared by the FDA as a 510(k) Class II Medical Device to filter out and inactivate airborne virus and bacteria within large rooms and indoor spaces. It is a free-standing, portable recirculating air cleaning system designed for additional front-line protection in healthcare settings.*

 **FDA Cleared**  
510(k) Class II Medical Device

## MODEL

Defend 1050 - Floor standing, 2-wheeled base + handle, 5-speed fan setting with 6.6 ft power cord

## AREA COVERAGE

200 – 1,000 ft<sup>2</sup> (4 air changes per hour)  
400 – 2,000 ft<sup>2</sup> (2 air changes per hour)

## VOLUME TREATMENT

1,600 – 8,000 ft<sup>3</sup> ( 4 air changes per hour)  
3,200 – 16,000 ft<sup>3</sup> (2 air changes per hour)

## ELECTRICAL RATING

Single Phase, 100-120 VAC, 60 HZ  
Fuse rated at 120 VAC, 6.3 Amps  
Listed

## POWER CONSUMPTION

Maximum 396W

## CONSTRUCTION + COLOR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish

## DIMENSIONS + WEIGHT

36.2" (h) × 19.3" (w) × 23.2" (d)  
118.6 lbs

## ELECTRICAL CONNECTION

Switched and fused with a grounded, molded and detachable power cord



## DEFEND 1050 SPECIFICATIONS

---

### FAN AIR FLOW

Speed 1 = 107 CFM  
Speed 2 = 187 CFM  
Speed 3 = 257 CFM  
Speed 4 = 400 CFM  
Speed 5 = 533 CFM

### FILTERS

Stage 1: M5 30/30 filter  
Stage 2: HEPA H13 filter, MGA grade  
Stage 3: G4 carbon pleated filter

### QUALITY & SAFETY

Manufactured under ISO 9001, ISO 14001 & OHSAS 18001.  
IEC 60601-1, Third Edition  
IEC 60601-1-2, Fourth Edition  
UL 867 Safety for Electrostatic Air Cleaners  
FDA K200321.510(k) Class II Medical Device



### NOISE LEVEL

Speed 1 = 48 dBA  
Speed 2 = 56 dBA  
Speed 3 = 62 dBA  
Speed 4 = 70 dBA  
Speed 5 = 78 dBA

### OPERATING CONDITIONS

50 – 95 °F, 10 – 75% Relative Humidity

### SHIPPING STORAGE

41 – 122 °F, Maximum 95% Relative Humidity