



PT120

Platinum 1mm flexible temperature probe

The PT120 represents a significant advancement in temperature sensing technology. Its platinum construction ensures high accuracy and stability, making it ideal for precision measurement needs. The compact design allows for easy integration into a variety of systems without disturbance, and the quick response time enables real-time monitoring and control.


Functions & Technology

Ideal temperature probe for narrow openings down to 1 mm in diameter.

The industry standard PT-100 sensor is precise and stable over a wide temperature range.


PT120 is also particularly useful for controlling heated stages inside dishes and other sensitive heated devices. The probe can be placed on any surface, such as metal, glass, plastic etc.

The probe can also be useful to measure liquids provided that it is placed inside a water-tight pouch.



Specifications

Sensor type	Analog PT-100 temperature sensor (3 wire)
Measure range & accuracy	-50-50°C / 0,03°C accuracy possible.
Display resolution and update	0,01 °C, one update per second
T90 (min:sec)	0:25
Compliance	ISO/EN61010-1 - RoHS
Operating conditions	0-50°C / 5-95% RH
Cable length	1,7m (including 0,5m flat cable)
Materials	Flexible FR-4, Epoxy.
IP Class	IP50
Calibration	Delivered with factory calibration certificate. Accuracy +/- 0,1°C PT120 can be calibrated in accordance with ISO/IEC 17025. Calibration requires an adaptor. Part no: 115s001.



Ordering info

Part no: 120s002 - PT120 Platinum 1mm flexible temperature probe
Part no: 800s002 - Accredited calibration of 1 temperature sensor

Nilotech Aps.

Knudstrupvej 14 - DK-4270 Hoeng, Denmark
+45 30 32 32 96 - contact@nilotech.eu - www.nilotech.eu

Document
120d001_2